

# TECHNICAL DATA DIGEST

## TUNG-O-VAR VARNISH STAIN SPRAY PAINT MAHOGANY INTERIOR-EXTERIOR

### APPLICATION

#### SURFACE

##### PREPARATION:

New surfaces-sand smooth and wipe clean before starting application. Apply two (2) or three (3) coats until color desired is obtained. (Can be wiped off with a clean, lint-free cloth).

#### PREVIOUSLY

##### FINISHED SURFACES:

For best results, remove all finishes back to bare wood and refinish as for new work. For recoating over sound, aged finishes, first remove all wax, grease, oil, or other foreign matter by washing with paint thinner and then with water and detergent. When surface dries, sand well with medium fine sandpaper and wipe clean. Apply one (1) or two (2) coats of this product.

##### CLEAN UP:

Clean up over spray with mineral spirits.

##### APPLICATION:

Shake can vigorously for one minute after agitator ball rattles freely. Both object to be painted and paint should be at least 70° F (20° C). Hold can upright 10-12 inches from surface and spray short even strokes. Aim away from face. Several thin mist coats are better than on full wet coat. Shake can periodically while painting. If tip clogs, remove and clean.

**TECHNICAL DATA DIGEST**  
**TUNG-O-VAR VARNISH STAIN PAINT MAHOGANY (cont.)**

**PRECAUTIONS:**

**CAUTION! EXTREMELY FLAMMABLE.** Combustible. Contains methylene chloride, which has been shown to cause cancer in certain laboratory animals. Risk to your health depends on level and duration of exposure. Keep away from heat, sparks and open flame. Vapors may ignite explosively. Do not puncture or incinerate (burn) container. Use only with adequate ventilation. If you must use it in indoors, open windows and doors to ensure a continuous flow of fresh air during application and drying. Avoid prolonged contact with skin and breathing of vapor or spray mist. Close container after each use. **KEEP OUT OF THE REACH OF CHILDREN.**